

ODYSSÉ II EVOLUTION EPOS terminal with dual screen system



www.aures.com



HSD EXCLUSIVE
by POSLIGNE®



Odysse II Evolution is the latest generation of the Odysse integrated system by AURES, featuring a dual screen system (*now with a second screen – touch or non touch*) for interactive and digital signage applications.

This version of the all-in-one **Odysse II** terminal has a second screen (*touch or non-touch are available*) facing the customer, for digital display applications, which can be programmed to display images, text and informational content to customers during cash desk operations.

This second adjustable, 8.4" display (22 x 17.5cm overall) is located on the rear of the unit and connected to the system's motherboard, enabling real-time, effective communication to customers at retail outlets, leisure centers, bars, restaurants and hotels, for messages to have a direct, spontaneous impact.

Odysse II Evolution benefits from AURES's exclusive 'Clip'n Color' system - a series of 10 interchangeable polycarbonate colour clips located on the device, which can match retail store brand image and visual identity.

Combining design style and high performance, **Odysse II Evolution** incorporates the very best in POS technologies: INTEL Pentium Dual-Core processor, integrated RAID 1 controller, the **HSD Exclusive** software platform, 2GB DDR3 of RAM (*up to 4GB*) and more.

HSD Exclusive: this feature also allows the key data from an entire batch of terminals to

be centralised, automatically sending information via e-mail (*to a store chain's Information Systems Manager or Hotline*), for as many units and locations as required.




ODYSSÉ EVOLUTION *design and technology*

- +
- +
- +
- +
- +
- +
- +

COLOURS OF THE CLIPS

	cassis		tonic orange
	iris		carmine red
	silver		pure white
	kiwi		black piano
	mocha		indigo blue

COLOURS OF THE SYSTEM BASE

	pearl		graphite
---	-------	---	----------

MODEL ODYSSÉ II EVOLUTION

Processor	Intel Pentium Dual-Core E5300
Chipset	82 G41 + ICH 7
Memory (RAM)	2GB DDR3 DIMM up to 4GB (2 slots)
Graphics memory	Up to 1.7GB shared RAM
RAID 1 Controller	integrated (Hot Swap)
Hard disk drive(s)	1 x 2.5" HDD (2nd HDD optional)
Touchscreen	15 inches / ELO Touch screen
Resolution	1024 x 768

SECOND SCREEN

Swivelling LCD screen display - touch or non-touch
8.4" – 22 x 17.5cm including surround
LCD resolution: 800 x 600
LCD brightness: 230 cd/sqm - with LED
eTurbo Touch panel (for the 2nd screen touch version)
Directly connected to the motherboard

INPUTS / OUTPUTS


Front face	on/off switch 2 USB ports
Rear face	
USB	6 USB 2.0 ports
Serial/COM	4 COM type ports (DB9 type, 5V/12V configurable via BIOS)
PS2	1
Line output	1
Mike input	1
Giga LAN network connection	1
Cash drawer output	1 x RJ11 (12V / 24V)
Printer output	1 x 24V

OTHER FEATURES

Loudspeakers	2 integrated
Mini PCI-e port	integrated
Internal power supply	EU "Energy Star" compliant
Dimensions (W x D x H)	375 x 381 x 325 in tilted position
Weight	10.75kg including card reader
Materials	polycarbonate (frames, accessories and customer display)
Compatible Operating Systems	POSReady, Windows XP Pro, Windows 7, Linux, etc.

OPTIONS

Badge and magnetic card reader (MCR)	Biometric (fingerprint) and MCR reader
Dallas key reader	CD/DVD reader/burner
Combined Dallas key and magnetic card reader	WIFI
Contactless badge reader (MIFARE)	Additional HDD



Specifications are subject to change without notice

