

PAR//NER

CARE . TRUST . RESPONSIBILITY

All-in-one Touch POS Terminal PT-6315 Be independent



The PT-6315 All-in-One POS Touch Terminal is the perfect solution for different kind of businesses.

Its compact and elegant design fits into every POS environment and is extremely counter space saving.

As the PT-6315 is an All-in-One Terminal, it can be easy installed without extra modules, cables etc.

This POS terminal is perfect for everyone who wants to be independent and flexible.

Special Features

CPU Celeron 1037U 1.8GHZ 2M Intel Smart Cache dual core

Supports 18/24 bit LED backlight panel

BIOS setting selection of Power button function

2.5" type SATA HDD or SSD

External 180W adapter

Supports Windows 8.1

Integrated Epson 80 mm thermal printer

Optional

CD-70, CD-7220, CD-3220

Pole for 2nd display

All-in-one Touch Terminal PT-6315

Technical data

Item	PT-6315		
CPU	Intel® Celeron™ 1037U (1.8GHz, dual core, 2MB Intel Smart Cache), Fanless		
Chipset	NM70		
Memory	up to 16GB (DDR3)		
LCD	15" LCD, LED backlight		
Resolution	1024 x 768		
Touch	Resistive (PS/2 I/F)		
LCD Brightness	250 cd/m2		
Ethernet	Onboard 10/100/1000 BASE-T Gigabit Ethernet		
Storage	SATA 2.5" HDD, SATA SSD (option)		
I/O ports	external 4x COM external 4x USB 2.0 internal 4x USB 1x LPT 1x PS/2 1x RJ-45 Ethernet (LED) 1x RJ-11 port (2 cash drawer control) 1x Mini PCI-e 1x external VGA for 2nd monitor		
Operation System	POSReady 2009, POSReady 7, Windows 7, Windows XP, Windows 8.1, Linux (ubuntu, Fedora)		
Power Supply	AC100~240V/DC+12V, 15A,180 watt power adaptor		
Environment		Operating	Storage
	Temperature	0~40 °C	-20~60 °C
	Humidity	15% ~ 80%	15% ~ 80%
Dimension	345mm(B) x 321mm(D) x 256mm(H)		
Integrated Peripherals	Integrated 80 mm thermal printer 3-MSR Track		
Options	Wireless LAN Customer Displays: CD-70, CD-7220 or CD-3220		



15" LCD touch



Elegant design



Optional pole 2nd display



Compact and small foot print



Rear VFD customer display

